

COMMANDTOOLS

BUTANE - POWER GAS

Product number: 207078

INSTRUCTION MANUAL

SPECIFICATIONS

GAS	Butane	45% (106-97-8)
	Isobutane	28% (75-28-5)
	Propane	26% (74-98-6)
	UN2037	
GAS FITTING	Butane valve	
FUEL CARTRIDGE SIZE	200 g	
BURN TEMPERATURE	1760°C / 3200°F	

INSTRUCTIONS:

For use with specified appliances only. For use with Command Tools soldering irons and heating torches. Strictly follow usage instructions supplied with your appliance.

1. Before refilling appliance, ensure gas switch is off.
2. Hold the appliance in an upside down position.
3. Insert the refill nozzle into the appliance gas valve and push down.
4. Stop refilling when gas starts to overflow.
5. Do not refill gas while near ignition sources, heating appliances or combustible materials.

REFER TO THE SDS FOR FIRST AID MEASURES, FIRE FIGHTING MEASURES, ACCIDENTAL RELEASE MEASURES, HANDLING & STORAGE.

KEEP OUT OF REACH OF CHILDREN

DANGER

FLAMMABLE GAS UNDER PRESSURE.

DO NOT LEAVE IN DIRECT SUNLIGHT.

DO NOT REFILL.

DO NOT PUNCTURE / PIERCE / INCINERATE EVEN AFTER USE OR EMPTY.

DO NOT EXPOSE TO TEMPERATURES EXCEEDING 40°C (104°F).

DO NOT STORE IN THE BOOT OR GLOVE BOX OF YOUR VEHICLE.

KEEP OUT OF REACH OF CHILDREN.

FOLLOW INSTRUCTIONS SUPPLIED WITH THE APPLIANCES.

STORE IN A COOL DRY PLACE.

TO DISCARD, CONTACT YOUR LOCAL RECYCLE CENTRE.