

WARNING:

- Pressurized cartridge, contains gas: use with care.
- Protect from direct sunlight and do not expose to temperatures exceeding 50°C (122°F).
- Keep out of reach of children
- Only dispose of completely empty bottles.
- Dispose of correctly according to local council regulations.
- Do not pierce bottle or burn, even after use.
- Keep oil and grease away from regulator and bottle connection.
- USE in well ventilated areas only.
- Store in a well ventilated place.
- **WARNING:** This is a non refillable cartridge, DO NOT REFILL.

DANGER:

H280: Contains gas under pressure; may explode if heated

P410: Protect from sunlight

P403: Store in a well ventilated place

ALSO AVAILABLE:

Part No: 216012, CO² Welding Gas for welding mild steel.


Part No: 210023, Argon/CO² Welding Gas, for welding mild steel with a better finish.

KEEP OUT OF REACH OF CHILDREN



Distributed by
Companion Brands
Bundoora VIC. 3083
www.companionbrands.com.au

MADE IN ITALY



TFM969

PRESSURE: 60 BAR
CONTENTS: 60 LITRES (ARGON)
THREAD SIZE: M10 X 1 MALE

Trade flame

ARGON

Argon gas is used for MIG welding aluminium. It can also be used for general TIG welding. Increase the portability of your welding machine by using a disposable shielding gas. If you wish to weld mild steel simply change to the CO² cartridge



INSTRUCTIONS: Remove protective rubber cap from the top of the bottle. Screw the regulator onto the cartridge in a clockwise direction. Hand tighten only. DO NOT over tighten. If the gas does not flow remove and refit the regulator. Regulate to the required pressure. After use remove the regulator from the cartridge. The cartridge has a self sealing valve which will seal after the regulator is removed. **DO NOT REFILL. DISPOSABLE CARTRIDGE. REFILLING IS NOT ALLOWED.**

PRESSURE: 60 BAR
CONTENTS: 60 LITRES (ARGON)
THREAD SIZE: M10 X 1 MALE

Trade flame

ARGON

 KEMPER H
PW 60 BAR PH 165 BAR .93L
EN 12205 IT 0036 2011

**UN1006
ARGON
COMPRESSED
DO NOT REFILL
930ML**

