

# Tradeflame

## TF/ULTRA GAS®

### Disposable

400g / 14.1oz

#### DANGER HIGHLY FLAMMABLE GAS

Misuse can cause severe injury.  
Always read the label / manual and leak-test every connection before lighting the appliance.



**IMPORTANT - ALWAYS CHECK FOR GAS LEAKS BY SPRAYING GAS LEAK DETECTION SPRAY OR FOAM ON ALL CONNECTIONS PRIOR TO USE**



#### DANGER

- **EXTREMELY FLAMMABLE GAS.**
- **CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.**
- **KEEP AWAY FROM HEAT / SPARKS / OPEN FLAMES/HOT SURFACES. NO SMOKING.**
- **LEAKING GAS FIRE: DO NOT EXTINGUISH, UNLESS LEAK CAN BE STOPPED SAFELY.**
- **ELIMINATE ALL IGNITION SOURCES IF SAFE TO DO SO.**
- **PROTECT FROM SUNLIGHT. STORE IN A WELL-VENTILATED PLACE.**
- **FOLLOW INSTRUCTIONS SUPPLIED WITH APPLIANCES.**
- **USE ONLY WITH TORCHES DESIGNED FOR TF/ULTRA GAS® OR MAPP® GAS. NEVER USE WITH STANDARD PROPANE APPLIANCES SUCH AS LANTERNS, STOVES, TORCHES ETC.**
- **KEEP OUT OF REACH OF CHILDREN.**
- **REFER TO THE SDS FOR FIRST AID MEASURES, FIRE FIGHTING MEASURES, ACCIDENTAL RELEASE MEASURES AND HANDLING AND STORAGE.**

#### SPECIFICATIONS

- **Gas:** Propylene: ≥ 95% (115-07-01) \ UN 1077
- **Gas fitting:** BOM fitting
- **Fuel cartridge size:** 400g / 14.1oz

#### INSTRUCTIONS:

##### BEFORE USE

1. Check cartridge and torch seals. Never use with damaged or missing seals. Discard cartridge if dirt or rust particles are in valve area.
2. Turn off torch.
3. Hold cartridge upright while attaching torch.
4. Attach cartridge outdoors away from pilot lights, flames, sparks and other ignition sources. They can ignite leaking gas.
5. Hand tighten only. Never use tools to tighten. Over-tightening can damage seals.
6. Check for leaks. Spray **Tradeflame Leak Detection Spray (211634)** or **Tradeflame Leak Detection Foam (400023)** on connections. Look for bubbles. Listen for hiss of escaping gas. Feel for extreme cold. Smell for rotten egg odour. Do not use if leaking.
7. Read and follow torch instructions.

#### DURING USE

1. Use upright to prevent flare-ups or flashes. Never drop or throw cartridge.
2. If torch sputters or flares up, turn cartridge upright and turn off torch. Vent area to remove unburned gas. Slowly turn on. After hearing slight hiss, re-light.
3. Never use near pilot lights, flames, sparks, and other ignition sources. They can ignite leaking gas.

#### AFTER USE

1. Turn off torch. Let cool.
2. Detach torch when not in use.
3. Detach outdoors away from pilot lights, flames, sparks, and other ignition sources. They can ignite leaking gas.
4. Replace cap to keep valve clean.
5. Store the gas cartridge outdoors in a well ventilated area out of the reach of children. Any indoor storage area shall comply with AS/NZS 1596.

-20°C to +65°C

**DO NOT REMOVE OR DEFACE THIS LABEL**



Part No. 326439

9 312652 055804

## UN1077

### DO NOT REFILL

CN NBRK BATCH NO. SEE BASE  
PW12BAR PH23BAR 0.95L  
EN ISO 11118:2015

\*MAPP® is a registered Trademark of the Linde Group  
†Faster heat transfer than propane

**Tradeflame.com**

Distributed by  
TRADEPEM INDUSTRIAL PTY LTD