

# Tradeflame®

## SPECIFICATIONS

- **Gas:** Butane  $\geq$  45% (106-97-8)  
Isobutane  $\geq$  28% (75-28-5)  
Propane  $\geq$  26% (74-98-6)
- **Gas fitting:** Refill valve
- **Fuel cartridge size:** 200g
- **UN2037**
- **EN 417 Compliant**



## DANGER

- **EXTREMELY FLAMMABLE**
- **FLAMMABLE GAS UNDER PRESSURE**
- **DO NOT LEAVE IN DIRECT SUNLIGHT**
- **DO NOT REFILL**
- **DO NOT PUNCTURE/PIERCE/INCINERATE EVEN AFTER USE OR EMPTY**
- **DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE**
- **DO NOT EXPOSE TO TEMPERATURES EXCEEDING 40°C**
- **DO NOT STORE IN THE BOOT OR GLOVE BOX OF YOUR VEHICLE**
- **FOLLOW INSTRUCTIONS SUPPLIED WITH THE APPLIANCE**
- **STORE IN A COOL DRY PLACE**
- **TO DISCARD CONTACT YOUR LOCAL RECYCLING CENTRE**

**IMPORTANT:** Avoid exposing the cartridge to extreme heat, hot surfaces, sparks, open flames, direct sunlight or other ignition sources. Doing so can cause the cartridge to rupture. No smoking.

**REFER TO THE SDS FOR FIRST AID MEASURES, FIRE FIGHTING MEASURES, ACCIDENTAL RELEASE MEASURES AND HANDLING AND STORAGE.**

# BUTANE POWER GAS

## 200g



## INSTRUCTIONS

1. Strictly follow usage instructions supplied with your appliance.
2. Perform this operation in a well-ventilated area, free from ignition sources, heating appliance or combustible materials.
3. Always check for leaks before ignition. Spray **Tradeflame Leak Detection Spray (211634)** or **Tradeflame Leak Detection Foam (400023)** on connections. Look for bubbles. Listen for hiss of escaping gas. Feel for extreme cold. Smell for rotten egg odour. Do not use if leaking.
4. For use only with appliances that recommend this cartridge type.
5. Before refilling appliance, ensure gas switch is off.
6. Hold the appliance in an upside down position.
7. Insert the refill nozzle into the appliance gas valve and push down.
8. Stop refilling when gas starts to overflow.



**CAUTION:** For maximum protection, always wear safety goggles, gloves or other appropriate equipment.

## KEEP OUT OF REACH OF CHILDREN

**ALWAYS CHECK FOR LEAKS BEFORE USE  
SCAN THE QR CODE TO SEE HOW**



Part No. 326603

**Tradeflame.com**

tradeflame tradeflametools